

SmartFil

Art. No.: 64 650



Technical Data

Filter	
Filter stages	2
Filter method	Storage Filter
Filter surface	25 m ²
Type of filter	Safe Change Filter
Filter material	Non-woven polyester
Filter efficiency	> 99.5 %
Filter class	E12
Additional filters	Pre-filter (aluminum)
Basic data	
Extraction capacity	1100 m ³ /h
Weight	289 kg
Motor power	2hp
Power supply	115V, 60 Hz
Rated current	16.5 A
Control voltage	24 V, DC
Noise level	70 dB(A)
Additional information	
IFA-Certification	W3-Approved
Fan type	Radial fan
Exhaust arm type	flexible exhaust arm
Length of exhaust arm	7ft, 10ft, 14ft

Applications

- Suitable for all materials, including high alloy steel
- Medium levels of smoke and dust
- Frequent use
- Alternating workplaces

Benefits

- Exhaust arm requires less adjustment due to flow-optimized exhaust hood design
- Increased safety due to filter monitoring
- Increased safety with safe filter change
- Very economic due to long lasting high-capacity filters

Properties

- 360 degrees rotating exhaust hood with damper
- 25m² filter surface
- Compact and solid design
- W3/IFA certified
- Exhaust arm 4 m

Accessories

- Automatic start-stop
- Workplace lighting incl. on/off switch at the hood

